
Modena 301XX0309 17.06.2024 v.09.5 www.norlys.com





Type of luminaire				
Type of lumianire	Corner			
Photometric body	Uncovered light.			
Characteristics of the luminaire	Classic design luminaire, mounted on a telescopic lighting pole. Adjustable height 19302830mm. For lighting gardens, terraces and other architectural concepts.			
General information				
Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. EPDM cable gland.			
Mounting method	Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø240mm every 120°. Set contains: Art. 3012 - luminaire, Art. 3010 - lightning pole. Other accessories need to be purchased separately.			
Terminal	Connection terminal: max. 4x2,5mm ² , possibility to connect luminaire in loop max 4x2,5mm ² . A round wire in the isolation with a diameter of max @712,5mm.			
Type of light source	E27 lamp Replaceable light source by an end-user.			
Net / gross weight of luminaire	9,78kg / 12,82kg			
Technical data				
E27 lamp	LED A5567			
Luminaire wattage	LED max 9W			
Ta Rated temperature	+25°C, up to +50°C on request			
Accessories sold separately				
305ZX0009 🖉	Concreting anchor.			
306ZX0009	Ground anchor.			
Recommended light sources				
Osram LED Parathom Classic / Retrofit E27 Phil		Philips Master LEDb	Philips Master LEDbulb / Classic / CorePro E27	
Osram ECO PRO Classic 77<=>100W E27		Philips ECO Classic 70<=>100W E27		
Spare parts				
06380004	Lens			
Files to download				
Manual				
Indexes				
Index	Color		RAL	
301B	BLACK		9005	
301W	WHITE		9003	

Norlys AS P.B 1014 Hoff, 0218 Oslo Hovfaret 4B, 0275 Oslo Norway +47 24 12 40 11 firmapost@norlys.no





Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.